

Garant
Boring bar steel, right-hand, Shank Ø / insert size: 8/06 mm

Order data

Order number	260032 8/06
GTIN	4045197652225
Item class	21T

Description

Boring bar steel 8/06 mm Shank Ø D_s: 8 mm
 ISO code toolholder: A08H SCLCR/L06
 Cutting point / joint: 8 mm
 Setting angle κ: 95 degrees
 suitable indexable insert: CC.. 0602..
 Minimum pre-drill Ø D_{min}: 10 mm

Technical description

ISO code toolholder	A08H SCLCR/L06
Pack of insert screws	269028 5
Overhang L ₁	35 mm
Insert size	6 mm
Cutting point / joint	8 mm
Centre offset L ₃	6 mm
suitable indexable insert	CC.. 0602..
Minimum pre-drill Ø D _{min}	10 mm
Overall length L	100 mm
Clamping height L ₂	7 mm
Setting angle κ	95 degrees
Shank Ø D _s	8 mm

Application type	right-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269410
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 5	269028 5