

Garant
Boring bar steel, left-hand, Shank \varnothing / insert size: 12/06 mm

Order data

| | |
|--------------|---------------|
| Order number | 260033 12/06 |
| GTIN | 4045197652324 |
| Item class | 21T |

Description

Boring bar steel 12/06 mm Shank $\varnothing D_s$: 12 mm
 ISO code toolholder: A12L SCLCR/L06
 Setting angle κ : 95 degrees
 suitable indexable insert: CC.. 0602..
 Minimum pre-drill $\varnothing D_{\min}$: 16 mm
 Centre offset L_3 : 9 mm

Technical description

| | |
|--|----------------|
| Centre offset L_3 | 9 mm |
| suitable indexable insert | CC.. 0602.. |
| ISO code toolholder | A12L SCLCR/L06 |
| Pack of insert screws | 269028 22 |
| Insert size | 6 mm |
| Minimum pre-drill $\varnothing D_{\min}$ | 16 mm |
| Overall length L | 140 mm |
| Clamping height L_2 | 11 mm |
| Setting angle κ | 95 degrees |
| Shank $\varnothing D_s$ | 12 mm |
| Application type | left-hand |
| Boring depth up to | 3xD |

| | |
|-----------------|------------|
| Standard | DIN 8024 |
| Through-coolant | yes |
| Type of product | Boring bar |

Accessories

| | |
|--|------------|
| Set of insert screws Type 22 | 269028 22 |
| Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm | 659906 500 |
| Set of insert screws 10 pieces | 269440 |
| PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8 | 674248 TX8 |