

Garant
Boring bar steel, left-hand, Shank \varnothing / insert size: 16/09 mm

Order data

Order number	260033 16/09
GTIN	4045197652331
Item class	21T

Description

Boring bar steel 16/09 mm Shank \varnothing D_s : 16 mm
 ISO code toolholder: A16Q SCLCR/L09
 Setting angle κ : 95 degrees
 suitable indexable insert: CC.. 09T3..
 Minimum pre-drill \varnothing D_{min} : 20 mm
 Centre offset L_3 : 11 mm

Technical description

Minimum pre-drill \varnothing D_{min}	20 mm
Insert size	9 mm
ISO code toolholder	A16Q SCLCR/L09
Pack of insert screws	269028 14
suitable indexable insert	CC.. 09T3..
Centre offset L_3	11 mm
Overall length L	180 mm
Clamping height L_2	14 mm
Setting angle κ	95 degrees
Shank \varnothing D_s	16 mm
Application type	left-hand
Boring depth up to	3xD

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269420
Set of insert screws Type 14	269028 14
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15