

**Garant**
**Boring bar steel, left-hand, Shank  $\varnothing$  / insert size: 20/09 mm**

**Order data**

Order number	260033 20/09
GTIN	4045197652348
Item class	21T

**Description**

Boring bar steel 20/09 mm Shank  $\varnothing D_s$ : 20 mm  
 ISO code toolholder: A20R SCLCR/L09  
 Setting angle  $\kappa$ : 95 degrees  
 suitable indexable insert: CC.. 09T3..  
 Minimum pre-drill  $\varnothing D_{min}$ : 25 mm  
 Centre offset  $L_3$ : 13 mm

**Technical description**

Pack of insert screws	269028 14
Minimum pre-drill $\varnothing D_{min}$	25 mm
Insert size	9 mm
Centre offset $L_3$	13 mm
ISO code toolholder	A20R SCLCR/L09
suitable indexable insert	CC.. 09T3..
Overall length L	200 mm
Clamping height $L_2$	18 mm
Setting angle $\kappa$	95 degrees
Shank $\varnothing D_s$	20 mm
Application type	left-hand
Boring depth up to	3xD

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Set of insert screws Type 14	269028 14
Set of insert screws 10 pieces	269420
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500