

Garant
Boring bar steel, left-hand, Shank \varnothing / insert size: 40/12 mm

Order data

Order number	260033 40/12
GTIN	4045197652379
Item class	21T

Description

Boring bar steel 40/12 mm Shank \varnothing D_s : 40 mm
 ISO code toolholder: A40T SCLCR/L12
 Setting angle κ : 95 degrees
 suitable indexable insert: CC.. 1204..
 Minimum pre-drill \varnothing D_{min} : 49 mm
 Centre offset L_3 : 27 mm

Technical description

ISO code toolholder	A40T SCLCR/L12
Centre offset L_3	27 mm
suitable indexable insert	CC.. 1204..
Shim screw	269013 5
Shim	269005 6
Pack of insert screws	269028 20
Minimum pre-drill \varnothing D_{min}	49 mm
Insert size	12 mm
Overall length L	300 mm
Clamping height L_2	38.5 mm
Setting angle κ	95 degrees
Shank \varnothing D_s	40 mm

Application type	left-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws 10 pieces	269430
Shim screw	269210
Shim screw Type 5	269013 5
Set of insert screws Type 20	269028 20
Shim	269030
Shim Type 6	269005 6
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15