

Garant
Boring bar steel, left-hand, Shank \varnothing / insert size: 8/06 mm

Order data

Order number	260033 8/06
GTIN	4045197652300
Item class	21T

Description

Boring bar steel 8/06 mm Shank $\varnothing D_s$: 8 mm
 ISO code toolholder: A08H SCLCR/L06
 Cutting point / joint: 8 mm
 Setting angle κ : 95 degrees
 suitable indexable insert: CC.. 0602..
 Minimum pre-drill $\varnothing D_{min}$: 10 mm

Technical description

Centre offset L_3	6 mm
Cutting point / joint	8 mm
Insert size	6 mm
suitable indexable insert	CC.. 0602..
Pack of insert screws	269028 5
Overhang L_1	35 mm
ISO code toolholder	A08H SCLCR/L06
Minimum pre-drill $\varnothing D_{min}$	10 mm
Overall length L	100 mm
Clamping height L_2	7 mm
Setting angle κ	95 degrees
Shank $\varnothing D_s$	8 mm

Application type	left-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269410
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Set of insert screws Type 5	269028 5