Garant

eco screw-on toolholder, short, left-hand, Shank / insert size: 16/11 mm



Order data

Order number	260295 16/11
GTIN	4045197927163
Item class	21U

Description

Version:

GARANT eco system screw-on toolholder with internal coolant feed to the cutting edge. Cooling by means of precision nozzles effectively and efficiently reduces the thermal loading, since the coolant stream is optimally directed between the chip and cutting edge. This results in higher productivity, longer tool life and greater process reliability. With flank face cooling.

Note:

Coolant transfer only possible in conjunction with GARANT eco system toolholders No. 319001 – 319886 or for shank length < 125 mm plus No. 317900.

Through-coolant: yes ISO code toolholder: SDJCR/L 1616X11 suitable indexable insert: DC.. 11T3.. Functional width L_4 : 20 mm Head length L_1 : 29 mm Overall length L: 74 mm Pack of insert screws: 269023 3

Technical description

suitable indexable insert

DC.. 11T3..

Insert size	11 mm
Shim	269007 1
Overall length L	74 mm
Functional width L ₄	20 mm
ISO code toolholder	SDJCR/L 1616X11
Head length L ₁	29 mm
Shim screw	269013 1
Pack of insert screws	269023 3
Shank size	16 mm
Application type	left-hand
Standard	DIN ISO 5610
Through-coolant	yes
Setting angle κ	93 degrees
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx [®] , shank E 6.3 Torx [®] profile TX15	674248 TX15