

Garant
Boring bar carbide, right-hand, Shank \varnothing / insert size: 10/07 mm

Order data

Order number	260318 10/07
GTIN	4045197652669
Item class	21T

Description

Boring bar carbide 10/07 mm Shank $\varnothing D_s$: 10 mm
 ISO code toolholder: E10K SDUCR/L07
 Setting angle κ : 93 degrees
 suitable indexable insert: DC.. 0702..
 Minimum pre-drill $\varnothing D_{min}$: 12.5 mm
 Centre offset L_3 : 7 mm

Technical description

suitable indexable insert	DC.. 0702..
Centre offset L_3	7 mm
Minimum pre-drill $\varnothing D_{min}$	12.5 mm
Pack of insert screws	269028 7
ISO code toolholder	E10K SDUCR/L07
Insert size	7 mm
Overall length L	125 mm
Clamping height L_2	9.6 mm
Setting angle κ	93 degrees
Shank $\varnothing D_s$	10 mm
Application type	right-hand
Boring depth up to	8xD
Tool material	Carbide

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
Set of insert screws Type 7	269028 7
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500