

Garant
Boring bar carbide, right-hand, Shank \varnothing / insert size: 12/07 mm

Order data

Order number	260318 12/07
GTIN	4045197652676
Item class	21T

Description

Boring bar carbide 12/07 mm Shank $\varnothing D_s$: 12 mm
 ISO code toolholder: E12M SDUCR/L07
 Cutting point / joint: 12 mm
 Setting angle κ : 93 degrees
 suitable indexable insert: DC.. 0702..
 Minimum pre-drill $\varnothing D_{min}$: 15 mm

Technical description

Overhang L_1	75 mm
suitable indexable insert	DC.. 0702..
Insert size	7 mm
Centre offset L_3	9 mm
Pack of insert screws	269028 7
Minimum pre-drill $\varnothing D_{min}$	15 mm
Cutting point / joint	12 mm
ISO code toolholder	E12M SDUCR/L07
Overall length L	150 mm
Clamping height L_2	11.6 mm
Setting angle κ	93 degrees
Shank $\varnothing D_s$	12 mm
Application type	right-hand

Boring depth up to	8xD
Tool material	Carbide
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 7	269028 7
Boring bar set carbide	260324