

Garant
Boring bar carbide, right-hand, Shank \varnothing / insert size: 16/07 mm

Order data

| | |
|--------------|---------------|
| Order number | 260318 16/07 |
| GTIN | 4045197652683 |
| Item class | 21T |

Description

Boring bar carbide 16/07 mm Shank $\varnothing D_s$: 16 mm
 ISO code toolholder: E16R SDUCR/L07
 Setting angle κ : 93 degrees
 suitable indexable insert: DC.. 0702..
 Minimum pre-drill $\varnothing D_{min}$: 19 mm
 Centre offset L_3 : 11 mm

Technical description

| | |
|---|----------------|
| ISO code toolholder | E16R SDUCR/L07 |
| Pack of insert screws | 269028 7 |
| Minimum pre-drill $\varnothing D_{min}$ | 19 mm |
| Centre offset L_3 | 11 mm |
| suitable indexable insert | DC.. 0702.. |
| Insert size | 7 mm |
| Overall length L | 200 mm |
| Clamping height L_2 | 15.6 mm |
| Setting angle κ | 93 degrees |
| Shank $\varnothing D_s$ | 16 mm |
| Application type | right-hand |
| Boring depth up to | 8xD |
| Tool material | Carbide |

| | |
|-----------------|------------|
| Standard | DIN 8024 |
| Through-coolant | yes |
| Type of product | Boring bar |

Accessories

| | |
|--|------------|
| Set of insert screws Type 7 | 269028 7 |
| PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8 | 674248 TX8 |
| Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm | 659906 500 |
| Set of insert screws 10 pieces | 269413 |