

Garant
Boring bar carbide, right-hand, Shank \varnothing / insert size: 8/07 mm

Order data

Order number	260318 8/07
GTIN	4045197652652
Item class	21T

Description

Boring bar carbide 8/07 mm Shank $\varnothing D_s$: 8 mm
 ISO code toolholder: E08K SDUCR/L07
 Setting angle κ : 93 degrees
 suitable indexable insert: DC.. 0702..
 Minimum pre-drill $\varnothing D_{min}$: 12.5 mm
 Centre offset L_3 : 7.5 mm

Technical description

Pack of insert screws	269028 7
Minimum pre-drill $\varnothing D_{min}$	12.5 mm
Centre offset L_3	7.5 mm
Insert size	7 mm
suitable indexable insert	DC.. 0702..
ISO code toolholder	E08K SDUCR/L07
Overall length L	125 mm
Clamping height L_2	7.6 mm
Setting angle κ	93 degrees
Shank $\varnothing D_s$	8 mm
Application type	right-hand
Boring depth up to	8xD
Tool material	Carbide

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 7	269028 7
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8