

**Garant**
**Boring bar carbide, left-hand, Shank  $\varnothing$  / insert size: 10/07 mm**

**Order data**

Order number	260319 10/07
GTIN	4045197652713
Item class	21T

**Description**

Boring bar carbide 10/07 mm Shank  $\varnothing D_s$ : 10 mm  
 ISO code toolholder: E10K SDUCR/L07  
 Setting angle  $\kappa$ : 93 degrees  
 suitable indexable insert: DC.. 0702..  
 Minimum pre-drill  $\varnothing D_{min}$ : 12.5 mm  
 Centre offset  $L_3$ : 7 mm

**Technical description**

ISO code toolholder	E10K SDUCR/L07
Centre offset $L_3$	7 mm
Pack of insert screws	269028 7
Minimum pre-drill $\varnothing D_{min}$	12.5 mm
Insert size	7 mm
suitable indexable insert	DC.. 0702..
Overall length L	125 mm
Clamping height $L_2$	9.6 mm
Setting angle $\kappa$	93 degrees
Shank $\varnothing D_s$	10 mm
Application type	left-hand
Boring depth up to	8xD

Tool material	Carbide
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 7	269028 7
Set of insert screws 10 pieces	269413