

## Garant

### Boring bar carbide, left-hand, Shank $\varnothing$ / insert size: 12/07 mm



#### Order data

Order number	260319 12/07
GTIN	4045197652720
Item class	21T

#### Description

Boring bar carbide 12/07 mm Shank  $\varnothing D_s$ : 12 mm  
 ISO code toolholder: E12M SDUCR/L07  
 Setting angle  $\kappa$ : 93 degrees  
 suitable indexable insert: DC.. 0702..  
 Minimum pre-drill  $\varnothing D_{min}$ : 15 mm  
 Centre offset  $L_3$ : 9 mm

#### Technical description

suitable indexable insert	DC.. 0702..
ISO code toolholder	E12M SDUCR/L07
Insert size	7 mm
Pack of insert screws	269028 7
Centre offset $L_3$	9 mm
Minimum pre-drill $\varnothing D_{min}$	15 mm
Overall length L	150 mm
Clamping height $L_2$	11.6 mm
Setting angle $\kappa$	93 degrees
Shank $\varnothing D_s$	12 mm
Application type	left-hand
Boring depth up to	8xD

Tool material	Carbide
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Set of insert screws 10 pieces	269413
Set of insert screws Type 7	269028 7