

**Garant**
**Boring bar carbide, left-hand, Shank  $\varnothing$  / insert size: 16/07 mm**

**Order data**

Order number	260319 16/07
GTIN	4045197652737
Item class	21T

**Description**

Boring bar carbide 16/07 mm Shank  $\varnothing D_s$ : 16 mm

ISO code toolholder: E16R SDUCR/L07

Setting angle  $\kappa$ : 93 degrees

suitable indexable insert: DC.. 0702..

Minimum pre-drill  $\varnothing D_{min}$ : 19 mm

Centre offset  $L_3$ : 11 mm

**Technical description**

Minimum pre-drill $\varnothing D_{min}$	19 mm
suitable indexable insert	DC.. 0702..
Pack of insert screws	269028 7
ISO code toolholder	E16R SDUCR/L07
Insert size	7 mm
Centre offset $L_3$	11 mm
Overall length L	200 mm
Clamping height $L_2$	15.6 mm
Setting angle $\kappa$	93 degrees
Shank $\varnothing D_s$	16 mm
Application type	left-hand
Boring depth up to	8xD

Tool material	Carbide
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Set of insert screws 10 pieces	269413
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 7	269028 7