

Garant

Boring bar carbide, left-hand, Shank \varnothing / insert size: 8/07 mm



Order data

Order number	260319 8/07
GTIN	4045197652706
Item class	21T

Description

Boring bar carbide 8/07 mm Shank \varnothing D_s : 8 mm
 ISO code toolholder: E08K SDUCR/L07
 Setting angle κ : 93 degrees
 suitable indexable insert: DC.. 0702..
 Minimum pre-drill \varnothing D_{min} : 12.5 mm
 Centre offset L_3 : 7.5 mm

Technical description

Pack of insert screws	269028 7
Insert size	7 mm
Centre offset L_3	7.5 mm
ISO code toolholder	E08K SDUCR/L07
Minimum pre-drill \varnothing D_{min}	12.5 mm
suitable indexable insert	DC.. 0702..
Overall length L	125 mm
Clamping height L_2	7.6 mm
Setting angle κ	93 degrees
Shank \varnothing D_s	8 mm
Application type	left-hand
Boring depth up to	8xD

Tool material	Carbide
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Set of insert screws 10 pieces	269413
Set of insert screws Type 7	269028 7
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500