

Garant
Boring bar carbide, right-hand, Shank \varnothing / insert size: 20/11 mm

Order data

Order number	260320 20/11
GTIN	4045197877727
Item class	21T

Description

Boring bar carbide 20/11 mm Shank $\varnothing D_s$: 20 mm
 ISO code toolholder: E205 SDQCR/L11
 Setting angle κ : 107.5 degrees
 suitable indexable insert: DC.. 11T3..
 Minimum pre-drill $\varnothing D_{min}$: 25 mm
 Centre offset L_3 : 12.5 mm

Technical description

Clamping height L_2	18.9 mm
Minimum pre-drill $\varnothing D_{min}$	25 mm
Centre offset L_3	12.5 mm
Insert size	11 mm
Setting angle κ	107.5 degrees
Pack of insert screws	269028 8
suitable indexable insert	DC.. 11T3..
Overall length L	250 mm
ISO code toolholder	E205 SDQCR/L11
Shank $\varnothing D_s$	20 mm
Application type	right-hand
Boring depth up to	8xD

Tool material	Carbide
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws 10 pieces	269414
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Set of insert screws Type 8	269028 8