

Garant
Boring bar carbide, left-hand, Shank \varnothing / insert size: 10/07 mm

Order data

Order number	260321 10/07
GTIN	4045197877758
Item class	21T

Description

Boring bar carbide 10/07 mm Shank \varnothing D_s : 10 mm
 ISO code toolholder: E10K SDQCR/L07
 Setting angle κ : 107.5 degrees
 suitable indexable insert: DC.. 0702..
 Minimum pre-drill \varnothing D_{min} : 13 mm
 Centre offset L_3 : 7 mm

Technical description

suitable indexable insert	DC.. 0702..
Pack of insert screws	269028 7
Clamping height L_2	9.6 mm
ISO code toolholder	E10K SDQCR/L07
Overall length L	125 mm
Insert size	7 mm
Centre offset L_3	7 mm
Setting angle κ	107.5 degrees
Minimum pre-drill \varnothing D_{min}	13 mm
Shank \varnothing D_s	10 mm
Application type	left-hand
Boring depth up to	8xD

Tool material	Carbide
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Set of insert screws Type 7	269028 7