

Garant
Boring bar carbide, left-hand, Shank \varnothing / insert size: 16/07 mm

Order data

Order number	260321 16/07
GTIN	4045197877772
Item class	21T

Description

Boring bar carbide 16/07 mm Shank $\varnothing D_s$: 16 mm
 ISO code toolholder: E16R SDQCR/L07
 Setting angle κ : 107.5 degrees
 suitable indexable insert: DC.. 0702..
 Minimum pre-drill $\varnothing D_{min}$: 20 mm
 Centre offset L_3 : 10 mm

Technical description

Minimum pre-drill $\varnothing D_{min}$	20 mm
Centre offset L_3	10 mm
Insert size	7 mm
ISO code toolholder	E16R SDQCR/L07
Overall length L	200 mm
Pack of insert screws	269028 7
suitable indexable insert	DC.. 0702..
Clamping height L_2	15.6 mm
Setting angle κ	107.5 degrees
Shank $\varnothing D_s$	16 mm
Application type	left-hand
Boring depth up to	8xD

Tool material	Carbide
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Set of insert screws Type 7	269028 7
Set of insert screws 10 pieces	269413