

Garant
Boring bar carbide, left-hand, Shank \varnothing / insert size: 20/11 mm

Order data

Order number	260321 20/11
GTIN	4045197877789
Item class	21T

Description

Boring bar carbide 20/11 mm Shank $\varnothing D_s$: 20 mm
 ISO code toolholder: E20S SDQCR/L11
 Setting angle κ : 107.5 degrees
 suitable indexable insert: DC.. 11T3..
 Minimum pre-drill $\varnothing D_{min}$: 25 mm
 Centre offset L_3 : 12.5 mm

Technical description

Overall length L	250 mm
suitable indexable insert	DC.. 11T3..
ISO code toolholder	E20S SDQCR/L11
Insert size	11 mm
Clamping height L_2	18.9 mm
Setting angle κ	107.5 degrees
Pack of insert screws	269028 8
Minimum pre-drill $\varnothing D_{min}$	25 mm
Centre offset L_3	12.5 mm
Shank $\varnothing D_s$	20 mm
Application type	left-hand
Boring depth up to	8xD

Tool material	Carbide
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws Type 8	269028 8
Set of insert screws 10 pieces	269414
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15