

**Garant**
**Boring bar HSS, right-hand, Shank  $\varnothing$  / insert size: 10/07 mm**

**Order data**

Order number	260328 10/07
GTIN	4045197652799
Item class	21T

**Description**

Boring bar HSS 10/07 mm Shank  $\varnothing D_s$ : 10 mm  
 ISO code toolholder: AH10K SDQCR/L07  
 Setting angle  $\kappa$ : 107.5 degrees  
 suitable indexable insert: DC.. 0702..  
 Minimum pre-drill  $\varnothing D_{min}$ : 13 mm  
 Centre offset  $L_3$ : 7 mm

**Technical description**

Pack of insert screws	269028 7
Minimum pre-drill $\varnothing D_{min}$	13 mm
suitable indexable insert	DC.. 0702..
ISO code toolholder	AH10K SDQCR/L07
Insert size	7 mm
Centre offset $L_3$	7 mm
Head length $L_1$	20 mm
Overall length L	125 mm
Clamping height $L_2$	9 mm
Setting angle $\kappa$	107.5 degrees
Shank $\varnothing D_s$	10 mm
Application type	right-hand

Boring depth up to	5×D
Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Set of insert screws Type 7	269028 7
Set of insert screws 10 pieces	269413
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500