

Garant
Boring bar HSS, right-hand, Shank \varnothing / insert size: 12/07 mm

Order data

Order number	260328 12/07
GTIN	4045197652805
Item class	21T

Description

Boring bar HSS 12/07 mm Shank $\varnothing D_s$: 12 mm
 ISO code toolholder: AH12M SDQCR/L07
 Setting angle κ : 107.5 degrees
 suitable indexable insert: DC.. 0702..
 Minimum pre-drill $\varnothing D_{min}$: 16 mm
 Centre offset L_3 : 8.5 mm

Technical description

Head length L_1	20 mm
ISO code toolholder	AH12M SDQCR/L07
Insert size	7 mm
Centre offset L_3	8.5 mm
Minimum pre-drill $\varnothing D_{min}$	16 mm
Pack of insert screws	269028 7
suitable indexable insert	DC.. 0702..
Overall length L	150 mm
Clamping height L_2	11 mm
Setting angle κ	107.5 degrees
Shank $\varnothing D_s$	12 mm
Application type	right-hand

Boring depth up to	5×D
Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Set of insert screws Type 7	269028 7
Set of insert screws 10 pieces	269413
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500