

Garant
Boring bar HSS, right-hand, Shank \varnothing / insert size: 16/07 mm

Order data

Order number	260328 16/07
GTIN	4045197652812
Item class	21T

Description

Boring bar HSS 16/07 mm Shank \varnothing D_s: 16 mm
 ISO code toolholder: AH16Q SDQCR/L07
 Setting angle κ : 107.5 degrees
 suitable indexable insert: DC.. 0702..
 Minimum pre-drill \varnothing D_{min}: 20 mm
 Centre offset L₃: 10 mm

Technical description

suitable indexable insert	DC.. 0702..
Pack of insert screws	269028 7
Head length L ₁	30 mm
ISO code toolholder	AH16Q SDQCR/L07
Minimum pre-drill \varnothing D _{min}	20 mm
Centre offset L ₃	10 mm
Insert size	7 mm
Overall length L	180 mm
Clamping height L ₂	15 mm
Setting angle κ	107.5 degrees
Shank \varnothing D _s	16 mm
Application type	right-hand

Boring depth up to	5×D
Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 7	269028 7
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Set of insert screws 10 pieces	269413