

Garant
Boring bar HSS, left-hand, Shank \varnothing / insert size: 10/07 mm

Order data

Order number	260329 10/07
GTIN	4045197652843
Item class	21T

Description

Boring bar HSS 10/07 mm Shank \varnothing D_s: 10 mm
 ISO code toolholder: AH10K SDQCR/L07
 Setting angle κ : 107.5 degrees
 suitable indexable insert: DC.. 0702..
 Minimum pre-drill \varnothing D_{min}: 13 mm
 Centre offset L₃: 7 mm

Technical description

Centre offset L ₃	7 mm
Minimum pre-drill \varnothing D _{min}	13 mm
suitable indexable insert	DC.. 0702..
ISO code toolholder	AH10K SDQCR/L07
Pack of insert screws	269028 7
Insert size	7 mm
Head length L ₁	20 mm
Overall length L	125 mm
Clamping height L ₂	9 mm
Setting angle κ	107.5 degrees
Shank \varnothing D _s	10 mm
Application type	left-hand

Boring depth up to	5×D
Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 7	269028 7
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8