

Garant
Boring bar HSS, left-hand, Shank \varnothing / insert size: 16/07 mm

Order data

Order number	260329 16/07
GTIN	4045197652867
Item class	21T

Description

Boring bar HSS 16/07 mm Shank $\varnothing D_s$: 16 mm
 ISO code toolholder: AH16Q SDQCR/L07
 Setting angle κ : 107.5 degrees
 suitable indexable insert: DC.. 0702..
 Minimum pre-drill $\varnothing D_{min}$: 20 mm
 Centre offset L_3 : 10 mm

Technical description

Minimum pre-drill $\varnothing D_{min}$	20 mm
Head length L_1	30 mm
ISO code toolholder	AH16Q SDQCR/L07
Centre offset L_3	10 mm
Insert size	7 mm
suitable indexable insert	DC.. 0702..
Pack of insert screws	269028 7
Overall length L	180 mm
Clamping height L_2	15 mm
Setting angle κ	107.5 degrees
Shank $\varnothing D_s$	16 mm
Application type	left-hand

Boring depth up to	5×D
Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
Set of insert screws Type 7	269028 7
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8