

Garant
Boring bar HSS, left-hand, Shank \varnothing / insert size: 20/11 mm

Order data

Order number	260329 20/11
GTIN	4045197652874
Item class	21T

Description

Boring bar HSS 20/11 mm Shank $\varnothing D_s$: 20 mm
 ISO code toolholder: AH20R SDQCR/L11
 Setting angle κ : 107.5 degrees
 suitable indexable insert: DC.. 11T3..
 Minimum pre-drill $\varnothing D_{\min}$: 25 mm
 Centre offset L_3 : 12.5 mm

Technical description

ISO code toolholder	AH20R SDQCR/L11
Pack of insert screws	269028 8
Minimum pre-drill $\varnothing D_{\min}$	25 mm
Insert size	11 mm
Head length L_1	40 mm
Centre offset L_3	12.5 mm
suitable indexable insert	DC.. 11T3..
Overall length L	200 mm
Clamping height L_2	18 mm
Setting angle κ	107.5 degrees
Shank $\varnothing D_s$	20 mm
Application type	left-hand

Boring depth up to	5×D
Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws 10 pieces	269414
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Set of insert screws Type 8	269028 8