

Garant
Boring bar HSS, right-hand, Shank \varnothing / insert size: 10/07 mm

Order data

Order number	260332 10/07
GTIN	4045197652904
Item class	21T

Description

Boring bar HSS 10/07 mm Shank \varnothing D_s : 10 mm

ISO code toolholder: AH10K SDUCR/L07

Setting angle κ : 93 degrees

suitable indexable insert: DC.. 0702..

Minimum pre-drill \varnothing D_{min} : 14 mm

Centre offset L_3 : 9 mm

Technical description

Pack of insert screws	269028 7
ISO code toolholder	AH10K SDUCR/L07
Insert size	7 mm
Centre offset L_3	9 mm
Minimum pre-drill \varnothing D_{min}	14 mm
suitable indexable insert	DC.. 0702..
Overall length L	125 mm
Clamping height L_2	9 mm
Setting angle κ	93 degrees
Shank \varnothing D_s	10 mm
Application type	right-hand
Boring depth up to	5xD

Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 7	269028 7