

Garant
Boring bar HSS, right-hand, Shank \varnothing / insert size: 1012/07 mm

Order data

Order number	260332 1012/07
GTIN	4045197652911
Item class	21T

Description

Boring bar HSS 1012/07 mm Shank \varnothing D_s: 12 mm
 ISO code toolholder: AH1012K SDUCR/L07
 Setting angle κ : 93 degrees
 suitable indexable insert: DC.. 0702..
 Minimum pre-drill \varnothing D_{min}: 15.5 mm
 Centre offset L₃: 9 mm

Technical description

Neck width	10 mm
Overhang L ₁ recessed holders	28 mm
Pack of insert screws	269028 7
Minimum pre-drill \varnothing D _{min}	15.5 mm
Centre offset L ₃	9 mm
suitable indexable insert	DC.. 0702..
ISO code toolholder	AH1012K SDUCR/L07
Insert size	7 mm
Overall length L	125 mm
Clamping height L ₂	11 mm
Setting angle κ	93 degrees
Usable depth T	5 mm

Shank Ø D _s	12 mm
Application type	right-hand
Boring depth up to	5×D
Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 7	269028 7
Boring bar set HSS	260334