

Garant
Boring bar HSS, right-hand, Shank \varnothing / insert size: 16/07 mm

Order data

Order number	260332 16/07
GTIN	4045197652942
Item class	21T

Description

Boring bar HSS 16/07 mm Shank \varnothing D_s : 16 mm
 ISO code toolholder: AH16Q SDUCR/L07
 Setting angle κ : 93 degrees
 suitable indexable insert: DC.. 0702..
 Minimum pre-drill \varnothing D_{min} : 20 mm
 Centre offset L_3 : 10 mm

Technical description

suitable indexable insert	DC.. 0702..
Insert size	7 mm
Minimum pre-drill \varnothing D_{min}	20 mm
Centre offset L_3	10 mm
ISO code toolholder	AH16Q SDUCR/L07
Pack of insert screws	269028 7
Overall length L	180 mm
Clamping height L_2	15 mm
Setting angle κ	93 degrees
Shank \varnothing D_s	16 mm
Application type	right-hand
Boring depth up to	5xD

Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 7	269028 7