

Garant
Boring bar HSS, right-hand, Shank \varnothing / insert size: 20/11 mm

Order data

Order number	260332 20/11
GTIN	4045197652959
Item class	21T

Description

Boring bar HSS 20/11 mm Shank $\varnothing D_s$: 20 mm
 ISO code toolholder: AH20R SDUCR/L11
 Setting angle κ : 93 degrees
 suitable indexable insert: DC.. 11T3..
 Minimum pre-drill $\varnothing D_{min}$: 26 mm
 Centre offset L_3 : 16 mm

Technical description

suitable indexable insert	DC.. 11T3..
Centre offset L_3	16 mm
Insert size	11 mm
Pack of insert screws	269028 8
Minimum pre-drill $\varnothing D_{min}$	26 mm
ISO code toolholder	AH20R SDUCR/L11
Overall length L	200 mm
Clamping height L_2	18 mm
Setting angle κ	93 degrees
Shank $\varnothing D_s$	20 mm
Application type	right-hand
Boring depth up to	5xD

Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269414
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 8	269028 8