

Garant
Boring bar HSS, left-hand, Shank \varnothing / insert size: 0810/07 mm

Order data

Order number	260333 0810/07
GTIN	4045197652973
Item class	21T

Description

Boring bar HSS 0810/07 mm Shank \varnothing D_s: 10 mm
 ISO code toolholder: AH0810H SDUCR/L07
 Setting angle κ : 93 degrees
 suitable indexable insert: DC.. 0702..
 Minimum pre-drill \varnothing D_{min}: 12.5 mm
 Centre offset L₃: 7 mm

Technical description

Pack of insert screws	269028 7
Neck width	8 mm
Minimum pre-drill \varnothing D _{min}	12.5 mm
ISO code toolholder	AH0810H SDUCR/L07
suitable indexable insert	DC.. 0702..
Overhang L ₁ recessed holders	22 mm
Centre offset L ₃	7 mm
Insert size	7 mm
Overall length L	100 mm
Clamping height L ₂	9 mm
Setting angle κ	93 degrees
Usable depth T	5 mm

Shank $\varnothing D_s$	10 mm
Application type	left-hand
Boring depth up to	5xD
Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 7	269028 7
Boring bar set HSS	260335