

Garant
Boring bar HSS, left-hand, Shank \varnothing / insert size: 1012/07 mm

Order data

Order number	260333 1012/07
GTIN	4045197652997
Item class	21T

Description

Boring bar HSS 1012/07 mm Shank \varnothing D_s: 12 mm
 ISO code toolholder: AH1012K SDUCR/L07
 Setting angle κ : 93 degrees
 suitable indexable insert: DC.. 0702..
 Minimum pre-drill \varnothing D_{min}: 15.5 mm
 Centre offset L₃: 9 mm

Technical description

Insert size	7 mm
Pack of insert screws	269028 7
Centre offset L ₃	9 mm
ISO code toolholder	AH1012K SDUCR/L07
suitable indexable insert	DC.. 0702..
Neck width	10 mm
Overhang L ₁ recessed holders	28 mm
Minimum pre-drill \varnothing D _{min}	15.5 mm
Overall length L	125 mm
Clamping height L ₂	11 mm
Setting angle κ	93 degrees
Usable depth T	5 mm

Shank $\varnothing D_s$	12 mm
Application type	left-hand
Boring depth up to	5xD
Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Set of insert screws Type 7	269028 7
Boring bar set HSS	260335