

Garant
Boring bar HSS, left-hand, Shank \varnothing / insert size: 12/07 mm

Order data

Order number	260333 12/07
GTIN	4045197653000
Item class	21T

Description

Boring bar HSS 12/07 mm Shank $\varnothing D_s$: 12 mm
 ISO code toolholder: AH12M SDUCR/L07
 Setting angle κ : 93 degrees
 suitable indexable insert: DC.. 0702..
 Minimum pre-drill $\varnothing D_{min}$: 16 mm
 Centre offset L_3 : 8 mm

Technical description

Insert size	7 mm
ISO code toolholder	AH12M SDUCR/L07
Pack of insert screws	269028 7
Centre offset L_3	8 mm
Minimum pre-drill $\varnothing D_{min}$	16 mm
suitable indexable insert	DC.. 0702..
Overall length L	150 mm
Clamping height L_2	11 mm
Setting angle κ	93 degrees
Shank $\varnothing D_s$	12 mm
Application type	left-hand
Boring depth up to	5xD

Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Set of insert screws Type 7	269028 7