

Garant
Boring bar HSS, left-hand, Shank Ø / insert size: 1216/07 mm

Order data

Order number	260333 1216/07
GTIN	4045197653017
Item class	21T

Description

Boring bar HSS 1216/07 mm Shank Ø D_s: 16 mm
 ISO code toolholder: AH1216M SDUCR/L07
 Setting angle κ: 93 degrees
 suitable indexable insert: DC.. 0702..
 Minimum pre-drill Ø D_{min}: 19.5 mm
 Centre offset L₃: 11 mm

Technical description

Insert size	7 mm
Neck width	12 mm
Centre offset L ₃	11 mm
suitable indexable insert	DC.. 0702..
ISO code toolholder	AH1216M SDUCR/L07
Overhang L ₁ recessed holders	36 mm
Minimum pre-drill Ø D _{min}	19.5 mm
Pack of insert screws	269028 7
Overall length L	150 mm
Clamping height L ₂	15 mm
Setting angle κ	93 degrees
Usable depth T	5 mm

Shank $\varnothing D_s$	16 mm
Application type	left-hand
Boring depth up to	5xD
Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 7	269028 7
Boring bar set HSS	260335