



## Boring bar steel, right-hand, Shank Ø / insert size: 16/07 mm



### Order data

Order number	260338 16/07
GTIN	4960664579570
Item class	25U

### Description

#### Version:

Streamlined flutes for improved chip evacuation, reduced tendency to vibrate, stable machining conditions.

Through-coolant: yes

Shank Ø  $D_s$ : 16 mm

ISO code toolholder: A16Q SDUCR/L07

Cutting point / joint: 16 mm

Setting angle  $\kappa$ : 93 degrees

suitable indexable insert: DC.. 0702..

Minimum pre-drill Ø  $D_{min}$ : 20 mm

### Technical description

Cutting point / joint	16 mm
Centre offset $L_3$	11.7 mm
ISO code toolholder	A16Q SDUCR/L07
suitable indexable insert	DC.. 0702..
Minimum pre-drill Ø $D_{min}$	20 mm
Insert size	7 mm
Insert screw	269022 4
Overall length L	180 mm
Clamping height $L_2$	15 mm
Setting angle $\kappa$	93 degrees

Shank Ø D <sub>s</sub>	16 mm
Application type	right-hand
Boring depth up to	5×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Clamping screw	269407
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Clamping screw Type 4	269022 4