



Boring bar steel, right-hand, Shank Ø / insert size: 16/11 mm



Order data

Order number	260338 16/11
GTIN	4960664579594
Item class	25U

Description

Version:

Streamlined flutes for improved chip evacuation, reduced tendency to vibrate, stable machining conditions.

Through-coolant: yes

Shank Ø D_s : 16 mm

ISO code toolholder: A16Q SDUCR/L11

Cutting point / joint: 16 mm

Setting angle κ : 93 degrees

suitable indexable insert: DC.. 11T3..

Minimum pre-drill Ø D_{min} : 23 mm

Technical description

ISO code toolholder	A16Q SDUCR/L11
Minimum pre-drill Ø D_{min}	23 mm
Centre offset L_3	14.5 mm
Insert screw	269022 3
suitable indexable insert	DC.. 11T3..
Cutting point / joint	16 mm
Insert size	11 mm
Overall length L	180 mm
Clamping height L_2	15 mm
Setting angle κ	93 degrees

Shank Ø D _s	16 mm
Application type	right-hand
Boring depth up to	5×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Clamping screw	269406
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Clamping screw Type 3	269022 3