



Boring bar steel, left-hand, Shank \varnothing / insert size: 16/07 mm



Order data

Order number	260339 16/07
GTIN	4960664579587
Item class	25U

Description

Version:

Streamlined flutes for improved chip evacuation, reduced tendency to vibrate, stable machining conditions.

Through-coolant: yes

Shank \varnothing D_s : 16 mm

ISO code toolholder: A16Q SDUCR/L07

Cutting point / joint: 16 mm

Setting angle κ : 93 degrees

suitable indexable insert: DC.. 0702..

Minimum pre-drill \varnothing D_{min} : 20 mm

Technical description

suitable indexable insert	DC.. 0702..
Cutting point / joint	16 mm
ISO code toolholder	A16Q SDUCR/L07
Minimum pre-drill \varnothing D_{min}	20 mm
Insert size	7 mm
Centre offset L_3	11.7 mm
Insert screw	269022 4
Overall length L	180 mm
Clamping height L_2	15 mm
Setting angle κ	93 degrees

Shank Ø D _s	16 mm
Application type	left-hand
Boring depth up to	5×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Clamping screw	269407
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Clamping screw Type 4	269022 4