



## Boring bar steel, left-hand, Shank $\varnothing$ / insert size: 16/11 mm



### Order data

Order number	260339 16/11
GTIN	4960664579600
Item class	25U

### Description

#### Version:

Streamlined flutes for improved chip evacuation, reduced tendency to vibrate, stable machining conditions.

Through-coolant: yes

Shank  $\varnothing D_s$ : 16 mm

ISO code toolholder: A16Q SDUCR/L11

Cutting point / joint: 16 mm

Setting angle  $\kappa$ : 93 degrees

suitable indexable insert: DC.. 11T3..

Minimum pre-drill  $\varnothing D_{min}$ : 23 mm

### Technical description

Centre offset $L_3$	14.5 mm
Minimum pre-drill $\varnothing D_{min}$	23 mm
suitable indexable insert	DC.. 11T3..
ISO code toolholder	A16Q SDUCR/L11
Cutting point / joint	16 mm
Insert size	11 mm
Insert screw	269022 3
Overall length L	180 mm
Clamping height $L_2$	15 mm
Setting angle $\kappa$	93 degrees

Shank Ø D <sub>s</sub>	16 mm
Application type	left-hand
Boring depth up to	5×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Clamping screw	269406
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Clamping screw Type 3	269022 3