

Garant
Boring bar, steel, right-hand, Shank \varnothing / insert size: 10/07 mm

Order data

Order number	260340 10/07
GTIN	4045197877796
Item class	21T

Description

Boring bar, steel 10/07 mm Shank \varnothing D_s : 10 mm
 ISO code toolholder: A10K SDQCR/L07
 Setting angle κ : 107.5 degrees
 suitable indexable insert: DC.. 0702..
 Minimum pre-drill \varnothing D_{min} : 14 mm
 Centre offset L_3 : 7 mm

Technical description

Clamping height L_2	9 mm
Overall length L	125 mm
suitable indexable insert	DC.. 0702..
ISO code toolholder	A10K SDQCR/L07
Minimum pre-drill \varnothing D_{min}	14 mm
Insert size	7 mm
Centre offset L_3	7 mm
Setting angle κ	107.5 degrees
Pack of insert screws	269028 7
Shank \varnothing D_s	10 mm
Application type	right-hand
Boring depth up to	3xD

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 7	269028 7