

Garant

Boring bar, steel, right-hand, Shank \varnothing / insert size: 20/11 mm



Order data

Order number	260340 20/11
GTIN	4045197877826
Item class	21T

Description

Boring bar, steel 20/11 mm Shank \varnothing D_s : 20 mm
 ISO code toolholder: A20R SDQCR/L11
 Setting angle κ : 107.5 degrees
 suitable indexable insert: DC.. 11T3..
 Minimum pre-drill \varnothing D_{min} : 26 mm
 Centre offset L_3 : 13 mm

Technical description

suitable indexable insert	DC.. 11T3..
Overall length L	200 mm
Pack of insert screws	269028 8
Centre offset L_3	13 mm
Minimum pre-drill \varnothing D_{min}	26 mm
Clamping height L_2	18 mm
ISO code toolholder	A20R SDQCR/L11
Insert size	11 mm
Setting angle κ	107.5 degrees
Shank \varnothing D_s	20 mm
Application type	right-hand
Boring depth up to	3xD

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269414
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Set of insert screws Type 8	269028 8