

Garant

Boring bar, steel, right-hand, Shank \varnothing / insert size: 40/11 mm



Order data

Order number	260340 40/11
GTIN	4045197877857
Item class	21T

Description

Boring bar, steel 40/11 mm Shank $\varnothing D_s$: 40 mm
 ISO code toolholder: A40T SDQCR/L11
 Setting angle κ : 107.5 degrees
 suitable indexable insert: DC.. 11T3..
 Minimum pre-drill $\varnothing D_{min}$: 49 mm
 Centre offset L_3 : 27 mm

Technical description

suitable indexable insert	DC.. 11T3..
Pack of insert screws	269028 24
Shim	269005 3
Insert size	11 mm
Overall length L	300 mm
Minimum pre-drill $\varnothing D_{min}$	49 mm
Clamping height L_2	39 mm
Centre offset L_3	27 mm
Setting angle κ	107.5 degrees
ISO code toolholder	A40T SDQCR/L11
Shim screw	269013 4
Shank $\varnothing D_s$	40 mm

Application type	right-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269468
Shim	269010
Shim screw	269202
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Shim screw Type 4	269013 4
Set of insert screws Type 24	269028 24
Shim Type 3	269005 3