

Garant
Boring bar, steel, left-hand, Shank \varnothing / insert size: 10/07 mm

Order data

Order number	260341 10/07
GTIN	4045197877864
Item class	21T

Description

Boring bar, steel 10/07 mm Shank $\varnothing D_s$: 10 mm
 ISO code toolholder: A10K SDQCR/L07
 Setting angle κ : 107.5 degrees
 suitable indexable insert: DC.. 0702..
 Minimum pre-drill $\varnothing D_{min}$: 14 mm
 Centre offset L_3 : 7 mm

Technical description

Clamping height L_2	9 mm
Setting angle κ	107.5 degrees
ISO code toolholder	A10K SDQCR/L07
Minimum pre-drill $\varnothing D_{min}$	14 mm
Pack of insert screws	269028 7
Insert size	7 mm
Centre offset L_3	7 mm
suitable indexable insert	DC.. 0702..
Overall length L	125 mm
Shank $\varnothing D_s$	10 mm
Application type	left-hand
Boring depth up to	3xD

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Set of insert screws Type 7	269028 7