

Garant
Boring bar, steel, left-hand, Shank \varnothing / insert size: 16/07 mm

Order data

Order number	260341 16/07
GTIN	4045197877888
Item class	21T

Description

Boring bar, steel 16/07 mm Shank $\varnothing D_s$: 16 mm
 ISO code toolholder: A16Q SDQCR/L07
 Setting angle κ : 107.5 degrees
 suitable indexable insert: DC.. 0702..
 Minimum pre-drill $\varnothing D_{min}$: 22 mm
 Centre offset L_3 : 11 mm

Technical description

Overall length L	180 mm
Insert size	7 mm
ISO code toolholder	A16Q SDQCR/L07
Minimum pre-drill $\varnothing D_{min}$	22 mm
Centre offset L_3	11 mm
Pack of insert screws	269028 7
Setting angle κ	107.5 degrees
Clamping height L_2	14 mm
suitable indexable insert	DC.. 0702..
Shank $\varnothing D_s$	16 mm
Application type	left-hand
Boring depth up to	3xD

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Set of insert screws Type 7	269028 7