

## Garant

### Boring bar, steel, left-hand, Shank $\varnothing$ / insert size: 20/11 mm



#### Order data

Order number	260341 20/11
GTIN	4045197877895
Item class	21T

#### Description

Boring bar, steel 20/11 mm Shank  $\varnothing$   $D_s$ : 20 mm  
 ISO code toolholder: A20R SDQCR/L11  
 Setting angle  $\kappa$ : 107.5 degrees  
 suitable indexable insert: DC.. 11T3..  
 Minimum pre-drill  $\varnothing$   $D_{min}$ : 26 mm  
 Centre offset  $L_3$ : 13 mm

#### Technical description

Pack of insert screws	269028 8
Insert size	11 mm
ISO code toolholder	A20R SDQCR/L11
Centre offset $L_3$	13 mm
Overall length $L$	200 mm
suitable indexable insert	DC.. 11T3..
Clamping height $L_2$	18 mm
Minimum pre-drill $\varnothing$ $D_{min}$	26 mm
Setting angle $\kappa$	107.5 degrees
Shank $\varnothing$ $D_s$	20 mm
Application type	left-hand
Boring depth up to	3xD

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Set of insert screws 10 pieces	269414
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 8	269028 8