

**Garant**
**Boring bar, steel, left-hand, Shank  $\varnothing$  / insert size: 25/11 mm**

**Order data**

Order number	260341 25/11
GTIN	4045197877901
Item class	21T

**Description**

Boring bar, steel 25/11 mm Shank  $\varnothing D_s$ : 25 mm  
 ISO code toolholder: A25R SDQCR/L11  
 Setting angle  $\kappa$ : 107.5 degrees  
 suitable indexable insert: DC.. 11T3..  
 Minimum pre-drill  $\varnothing D_{min}$ : 32.5 mm  
 Centre offset  $L_3$ : 17 mm

**Technical description**

Centre offset $L_3$	17 mm
Setting angle $\kappa$	107.5 degrees
Pack of insert screws	269028 8
ISO code toolholder	A25R SDQCR/L11
Clamping height $L_2$	24 mm
Minimum pre-drill $\varnothing D_{min}$	32.5 mm
Overall length $L$	200 mm
Insert size	11 mm
suitable indexable insert	DC.. 11T3..
Shank $\varnothing D_s$	25 mm
Application type	left-hand
Boring depth up to	3xD

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Set of insert screws 10 pieces	269414
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Set of insert screws Type 8	269028 8