

**Garant**
**Boring bar, steel, left-hand, Shank  $\varnothing$  / insert size: 32/11 mm**

**Order data**

Order number	260341 32/11
GTIN	4045197877918
Item class	21T

**Description**

Boring bar, steel 32/11 mm Shank  $\varnothing$  D<sub>3</sub>: 32 mm  
 ISO code toolholder: A32S SDQCR/L11  
 Setting angle  $\kappa$ : 107.5 degrees  
 suitable indexable insert: DC.. 11T3..  
 Minimum pre-drill  $\varnothing$  D<sub>min</sub>: 44 mm  
 Centre offset L<sub>3</sub>: 22 mm

**Technical description**

Centre offset L <sub>3</sub>	22 mm
Shim	269005 3
Clamping height L <sub>2</sub>	31 mm
Setting angle $\kappa$	107.5 degrees
suitable indexable insert	DC.. 11T3..
Pack of insert screws	269028 24
Shim screw	269013 4
Insert size	11 mm
Overall length L	250 mm
Minimum pre-drill $\varnothing$ D <sub>min</sub>	44 mm
ISO code toolholder	A32S SDQCR/L11
Shank $\varnothing$ D <sub>s</sub>	32 mm

Application type	left-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

## Accessories

Shim screw	269202
Shim	269010
Set of insert screws 10 pieces	269468
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Shim screw Type 4	269013 4
Shim Type 3	269005 3
Set of insert screws Type 24	269028 24