

Garant
Boring bar steel, right-hand, Shank \varnothing / insert size: 10/07 mm

Order data

Order number	260342 10/07
GTIN	4045197656032
Item class	21T

Description

Boring bar steel 10/07 mm Shank $\varnothing D_s$: 10 mm
 ISO code toolholder: A10K SDUCR/L07
 Cutting point / joint: 10 mm
 Setting angle κ : 93 degrees
 suitable indexable insert: DC.. 0702..
 Minimum pre-drill $\varnothing D_{min}$: 13.5 mm

Technical description

Centre offset L_3	7 mm
Cutting point / joint	10 mm
Overhang L_1	40 mm
Pack of insert screws	269028 7
Insert size	7 mm
Minimum pre-drill $\varnothing D_{min}$	13.5 mm
suitable indexable insert	DC.. 0702..
ISO code toolholder	A10K SDUCR/L07
Overall length L	125 mm
Clamping height L_2	9 mm
Setting angle κ	93 degrees
Shank $\varnothing D_s$	10 mm

Application type	right-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Set of insert screws Type 7	269028 7