

**Garant**
**Boring bar steel, right-hand, Shank  $\varnothing$  / insert size: 20/11 mm**

**Order data**

Order number	260342 20/11
GTIN	4045197653093
Item class	21T

**Description**

Boring bar steel 20/11 mm Shank  $\varnothing D_s$ : 20 mm  
 ISO code toolholder: A20R SDUCR/L11  
 Setting angle  $\kappa$ : 93 degrees  
 suitable indexable insert: DC.. 11T3..  
 Minimum pre-drill  $\varnothing D_{min}$ : 25 mm  
 Centre offset  $L_3$ : 13 mm

**Technical description**

suitable indexable insert	DC.. 11T3..
Centre offset $L_3$	13 mm
Insert size	11 mm
Pack of insert screws	269028 8
ISO code toolholder	A20R SDUCR/L11
Minimum pre-drill $\varnothing D_{min}$	25 mm
Overall length L	200 mm
Clamping height $L_2$	18 mm
Setting angle $\kappa$	93 degrees
Shank $\varnothing D_s$	20 mm
Application type	right-hand
Boring depth up to	3xD

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 8	269028 8
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Set of insert screws 10 pieces	269414