

Garant
Boring bar steel, right-hand, Shank \varnothing / insert size: 40/11 mm

Order data

Order number	260342 40/11
GTIN	4045197656056
Item class	21T

Description

Boring bar steel 40/11 mm Shank $\varnothing D_s$: 40 mm
 ISO code toolholder: A40T SDUCR/L11
 Setting angle κ : 93 degrees
 suitable indexable insert: DC.. 11T3..
 Minimum pre-drill $\varnothing D_{min}$: 49 mm
 Centre offset L_3 : 27 mm

Technical description

Shim	269005 3
Pack of insert screws	269028 24
ISO code toolholder	A40T SDUCR/L11
Centre offset L_3	27 mm
Shim screw	269013 4
Minimum pre-drill $\varnothing D_{min}$	49 mm
Insert size	11 mm
suitable indexable insert	DC.. 11T3..
Overall length L	300 mm
Clamping height L_2	39 mm
Setting angle κ	93 degrees
Shank $\varnothing D_s$	40 mm

Application type	right-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws Type 24	269028 24
Shim screw Type 4	269013 4
Shim screw	269202
Set of insert screws 10 pieces	269414
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Set of insert screws 10 pieces	269468
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 8	269028 8
Shim	269010
Shim Type 3	269005 3