

Garant
Boring bar steel, left-hand, Shank \varnothing / insert size: 16/07 mm

Order data

Order number	260343 16/07
GTIN	4045197653123
Item class	21T

Description

Boring bar steel 16/07 mm Shank $\varnothing D_s$: 16 mm
 ISO code toolholder: A16Q SDUCR/L07
 Setting angle κ : 93 degrees
 suitable indexable insert: DC.. 0702..
 Minimum pre-drill $\varnothing D_{min}$: 20 mm
 Centre offset L_3 : 11 mm

Technical description

Centre offset L_3	11 mm
Pack of insert screws	269028 7
Minimum pre-drill $\varnothing D_{min}$	20 mm
suitable indexable insert	DC.. 0702..
Insert size	7 mm
ISO code toolholder	A16Q SDUCR/L07
Overall length L	180 mm
Clamping height L_2	14 mm
Setting angle κ	93 degrees
Shank $\varnothing D_s$	16 mm
Application type	left-hand
Boring depth up to	3xD

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws Type 7	269028 7
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Set of insert screws 10 pieces	269413