

**Garant**
**Boring bar steel, left-hand, Shank  $\varnothing$  / insert size: 32/11 mm**

**Order data**

Order number	260343 32/11
GTIN	4045197656018
Item class	21T

**Description**

Boring bar steel 32/11 mm Shank  $\varnothing D_s$ : 32 mm  
 ISO code toolholder: A32S SDUCR/L11  
 Setting angle  $\kappa$ : 93 degrees  
 suitable indexable insert: DC.. 11T3..  
 Minimum pre-drill  $\varnothing D_{min}$ : 40 mm  
 Centre offset  $L_3$ : 22 mm

**Technical description**

Pack of insert screws	269028 24
Shim screw	269013 4
suitable indexable insert	DC.. 11T3..
Shim	269005 3
Centre offset $L_3$	22 mm
ISO code toolholder	A32S SDUCR/L11
Minimum pre-drill $\varnothing D_{min}$	40 mm
Insert size	11 mm
Overall length L	250 mm
Clamping height $L_2$	31 mm
Setting angle $\kappa$	93 degrees
Shank $\varnothing D_s$	32 mm

Application type	left-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

## Accessories

Set of insert screws Type 8	269028 8
Set of insert screws Type 24	269028 24
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Shim screw Type 4	269013 4
Shim screw	269202
Shim Type 3	269005 3
Shim	269010
Set of insert screws 10 pieces	269468
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws 10 pieces	269414